


A


Top / Bottom Hole \varnothing 3,2 mm
Panel Thickness 1,6 mm

B




Type A

YP-1132-xx
PCB Post /PCB Support/ Spacer
with Locking Two Prong



Type B

YP-1232-xx
One side locked
one side removable



Type C

YP-1332-xx
Double Side Removable

C


Material	PA6 GF15 UL94 V2	Top/Bottom Panel Thickness	min : 1,57 mm max: 1,65 mm
Color	Naturel	\varnothing Top / Bottom Hole	3,20 mm

D

Code	Lenght (L mm)	Top / Bottom Hole (mm)	Panel Thickness (mm)	Type
YP-1132-05	5	\varnothing 3,20	1,60	A
YP-1132-10	10	\varnothing 3,20	1,60	A
YP-1132-15	15	\varnothing 3,20	1,60	A
YP-1132-20	20	\varnothing 3,20	1,60	A
YP-1232-05	5	\varnothing 3,20	1,60	B
YP-1232-10	10	\varnothing 3,20	1,60	B
YP-1232-15	15	\varnothing 3,20	1,60	B
YP-1232-20	20	\varnothing 3,20	1,60	B
YP-1332-05	5	\varnothing 3,20	1,60	C
YP-1332-10	10	\varnothing 3,20	1,60	C
YP-1332-15	15	\varnothing 3,20	1,60	C
YP-1332-20	20	\varnothing 3,20	1,60	C

E

F

NAME	DATE	ARTICLE NO:	REVISION:	TITLE:
DRAWN	Dursun Daşdemir	25.06.21		Geçmeli Yükseltme Parçaları
CHECKED	Ali Altınışık	25.06.21		
COMMENTS:				DWG NO.
This drawing is subject to technical modification without prior notice. Typographical and other errors do not justify any claims for damages. All dimensions should be verified using an actual produced part				
 ALTINKAYA ENCLOSURES FOR ELECTRONICS www.altinkaya.com.tr				YP Serisi
<small>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTINKAYA ENCLOSURES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTINKAYA ENCLOSURES IS PROHIBITED.</small>				
MATERIAL: PA66 UL94 V2				SCALE:3:1
WEIGHT:				SHEET 1 OF 1
				A4
				